



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Edge protectors are used wherever metal edges must be blunted or covered. Additional machining is not required. The edge guards also have a decorative effect and are flexible. The U-shaped metal clamps embedded in PVC ensure that the edge guards fit securely, even when the metal edge to be covered is curved inward or outward.

The guard is simply pressed into position by hand. Tools, adhesives or other connections are not required. Edge guards are available in different shapes, sizes, colours and finishes, depending on the intended use.

Combination sealing sections are PVC edge guards with bonded-on microcellular rubber sections and embedded metal clamping strips. These sections are made of microcellular rubber in the sealing area (EPDM quality) and of PVC in the clamping area. EPDM qualities are high-quality synthetic rubbers and are characterised by high resistance to ageing and good elasticity.

Rubber combination sealing sections are flexible edge guards made of soft rubber with embedded metal clamping strips.

These sections are made of microcellular rubber in the sealing area (EPDM quality) and of soft rubber (EPDM quality) in the clamping area.

The two materials are extrusion-vulcanised and bonded. Oil-resistant are available on request.

Tolerances:

Microcellular rubber sections **DIN 7715 E 3**

Soft rubber sections **DIN 7715 E 2**

PVC sections **DIN 16941**

Tolerances for cut lengths as agreed

Packaging

Cut lengths, enclosed frames (corner-vulcanised) and rings.

The flange can be filled with plastic sealants (on request). Ask for our quotation.

Custom designs

If the cross-sections illustrated here do not suit your requirements, the appropriate section can be custom-designed for you.

We would be happy to advise you and draw up a suitable design for your needs.

On request we can add flocking to rubber sections.



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Edge protectors made of PVC with embedded steel clamping strips

Design	Bend radius	Item no.	Technical data
		161 0460* black 161 0450* white 161 0520* grey	Clamping range: 0.8–1.0 mm Soft PVC Steel clamping strip Sales unit: 100 m
		161 0465*	Clamping range: 2.0 mm Soft PVC black Steel clamping strip Sales unit: 100 m
		161 0440*	Clamping range: 0.8–1.0 mm Soft PVC black Steel clamping strip Sales unit: 100 m
		161 0620* white grey 161 0825* black 161 0470* silver grey	Clamping range: 1.0–2.5 mm Soft PVC Steel clamping strip Sales unit: 100 m
		161 0826*	Clamping range: 1.0–2.0 mm Soft PVC Steel clamping strip Sales unit: 100 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Edge protectors made of PVC with embedded steel clamping strips

Design	Bend radius	Item no.	Technical data
		161 0823*	Clamping range: 1.0–3.0 mm Soft PVC black Steel clamping strip Sales unit: 100 m
		161 0824*	Clamping range: 1.0–3.0 mm Soft PVC black Steel clamping strip Sales unit: 100 m
		161 0329*	Clamping range: 3.5 mm Soft PVC black Steel clamping strip Sales unit: 100 m
		161 9630	Clamping range: 1.0–2.5 mm Soft PVC black Steel clamping strip Sales unit: 100 m
		161 9885	Clamping range: 1.0–2.5 mm Soft PVC black Steel clamping strip Sales unit: 100 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Edge protectors made of PVC with embedded steel clamping strips

Design	Bend radius	Item no.	Technical data
		161 0327*	Clamping range: 3.5 mm Soft PVC black Steel clamping strip Sales unit: 100 m
		161 0326* black 161 0720* anthracite 161 0920* light grey	Clamping range: 1.0–4.0 mm Soft PVC Steel clamping strip Sales unit: 100 m
		161 0135*	Clamping range: 4.0–6.0 mm Soft PVC black Steel clamping strip Sales unit: 100 m
		161 0134 light grey 161 0130* black	Clamping range: 1.0–4.5 mm Soft PVC Steel clamping strip Sales unit: 100 m
		161 0325*	Clamping range: 1.0–4.5 mm Soft PVC black Steel clamping strip Sales unit: 100 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Edge protectors made of PVC with embedded steel clamping strips

Design	Bend radius	Item no.	Technical data
		161 0360* black 161 0740* light grey	Clamping range: 6.0–8.0 mm Soft PVC Steel clamping strip Sales unit: 100 m
		161 9508*	Clamping range: 10.0 mm Soft PVC light grey Steel clamping strip Sales unit: 100 m



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Edge protectors made of PVC with embedded ABS clamping strips

Design	Bend radius	Item no.	Technical data
		165 9001 black 165 9002 light grey	Clamping range: 1.0–2.0 mm Soft PVC ABS clamping strip Sales unit: 100 m
		165 9003 black 165 9004 light grey	Clamping range: 1.0–2.0 mm Soft PVC ABS clamping strip Sales unit: 100 m
		165 9021	Clamping range: 1.5–3.5 mm Soft PVC black ABS clamping strip Sales unit: 100 m
		165 9005	Clamping range: 1.5–3.5 mm TPE/PVC black POM clamping strip Sales unit: 100 m



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Edge protectors made of solid rubber

Design	Bend radius	Item no.	Technical data
		161 9767	Clamping range: 1.0–3.0 mm EPDM soft rubber black Wire clamping strip Sales unit: 100 m
		161 9766	Clamping range: 2.0–4.0 mm EPDM soft rubber black Wire clamping strip Sales unit: 100 m
		161 9758	Clamping range: 4.0–5.0 mm EPDM soft rubber black Wire clamping strip Sales unit: 50 m
		161 9673	Clamping range: 1.0 mm EPDM soft rubber black Wire clamping strip Sales unit: 50 m
		161 9740	Clamping range: 2.0–4.0 mm EPDM soft rubber black Steel clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Combination sealing sections made of PVC with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
	R60	161 0960*	Clamping range: 1.0–2.0 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 100 m
	R120 R80 R30	161 0840*	Clamping range: 1.5–3.5 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m
	R70 R80 R20	161 9798 PVC/EPDM microcellular rubber 161 9799 PVC/CR microcellular rubber	Clamping range: 1.5–4.0 mm black Steel clamping strip Sales unit: 50 m
	R70 R80 R30	161 9800	Clamping range: 1.5–5.0 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m
	R80 R100 R20	161 9804	Clamping range: 1.0–4.0 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Combination sealing sections made of PVC with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 9626*	Clamping range: 2.0–3.5 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9805	Clamping range: 1.0–4.0 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9558*	Clamping range: 4.0–7.0 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 0843*	Clamping range: 2.0–3.5 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request

* Available from stock

Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Combination sealing sections made of PVC with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 9632	Clamping range: 1.0–3.5 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9802	Clamping range: 1.0–4.0 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9627	Clamping range: 1.0–2.5 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9803	Clamping range: 1.0–3.5 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request

* Available from stock

Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Combination sealing sections made of PVC with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 9127*	Clamping range: 1.5–3.5 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 0950	Clamping range: 1.0–2.0 mm PVC soft/EPDM- microcellular rubber black Metal clamping strip Sales unit: 50 m
		161 9768	Clamping range: 1.0–2.0 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9599*	Clamping range: 2.0–4.0 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9631*	Clamping range: 1.0–3.0 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Combination sealing sections made of PVC with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 9772	Clamping range: 1.0–3.5 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9773	Clamping range: 2.0–4.0 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 0154*	Clamping range: 1.5–3.5 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9742*	Clamping range: 1.0–2.5 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9769	Clamping range: 2.0–3.0 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Combination sealing sections made of PVC with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 9771	Clamping range: 2.0–4.0 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9770	Clamping range: 2.0–3.5 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9622	Clamping range: 0.5–2.5 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 0153*	Clamping range: 1.5–3.5 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9780	Clamping range: 1.0–4.0 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Combination sealing sections made of PVC with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 0660*	Clamping range: 1.0–3.5 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9783	Clamping range: 2.0–5.0 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9774	Clamping range: 1.0–3.5 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9778	Clamping range: 1.0–3.5 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9779	Clamping range: 2.0–4.0 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Combination sealing sections made of PVC with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 9787	Clamping range: 1.5–4.0 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9785	Clamping range: 1.5–4.0 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9784	Clamping range: 1.0–3.5 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9782	Clamping range: 2.0–4.0 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9447*	Clamping range: 1.0–3.5 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Combination sealing sections made of PVC with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 9507*	Clamping range: 3.5 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9614	Clamping range: 1.0–4.5 mm PVC/EPDM microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9781	Clamping range: 1.0–4.0 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9790	Clamping range: 2.0–4.0 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9613*	Clamping range: 2.0–4.5 mm PVC/EPDM microcellular rubber black Wire clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Combination sealing sections made of PVC with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 9612*	Clamping range: 2.0–4.5 mm PVC/EPDM microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9791	Clamping range: 6.0–8.0 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9792	Clamping range: 2.0–4.0 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9793	Clamping range: 2.0–4.0 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9263*	Clamping range: 1.0–4.0 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Combination sealing sections made of PVC with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 9633*	Clamping range: 4.0–7.0 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9794	Clamping range: 1.0–3.5 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9795	Clamping range: 1.5–4.0 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9796	Clamping range: 1.5–4.0 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 0641*	Clamping range: 1.0–3.5 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Combination sealing sections made of PVC with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 9901	Clamping range: 1.0–3.5 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 0550* Clamping range: 2.0–4.5 mm 161 9663* Clamping range: 1.0–2.5 mm	PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 25 m
		161 9806	Clamping range: 1.0–4.0 mm PVC/EPDM microcellular rubber black Steel clamping strip Sales unit: 100 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request

* Available from stock

Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Combination sealing sections made of PVC with embedded metal clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		170 9865	Clamping range: 1.0–3.5 mm PVC/PUR foam black Steel clamping strip Length: 1.44 m



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Combination sealing sections made of PVC with embedded ABS clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
	R60	165 9029	Clamping range: 1.0–2.0 mm Soft TPE/TPE/ microcellular rubber black ABS clamping strip Sales unit: 50 m
	R30	165 9026	Clamping range: 1.5–2.5 mm PVC/EPDM microcellular rubber black ABS clamping strip Sales unit: 50 m
	R50	165 9027	Clamping range: 1.5–3.5 mm PVC/EPDM microcellular rubber black ABS clamping strip Sales unit: 50 m
	R50	165 9024	Clamping range: 1.5–3.5 mm PVC/EPDM microcellular rubber black ABS clamping strip Sales unit: 50 m
	R30	165 9022	Clamping range: 1.5–2.5 mm PVC/EPDM microcellular rubber black ABS clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Combination sealing sections made of PVC with embedded ABS clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		165 9030	Clamping range: 1.0–2.0 mm Soft TPE/TPE/ microcellular rubber black ABS clamping strip Sales unit: 50 m
		165 9025	Clamping range: 1.5–3.5 mm PVC/EPDM microcellular rubber black ABS clamping strip Sales unit: 50 m
		165 9023	Clamping range: 1.5–3.5 mm PVC/EPDM microcellular rubber black ABS clamping strip Sales unit: 50 m
		165 9028	Clamping range: 1.5–3.5 mm PVC/brush black ABS clamping strip Sales unit: 50 m
		165 9020	Clamping range: 4,0-5,0 mm PVC/EPDM microcellular rubber black ABS clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil®

TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Ausführung	Biegeradius	Artikel Nr.	techn. Daten
		165 9031	Clamping Range: 4,0-5,0 mm PVC/EPDM microcellular rubber black ABS clamping strip Sales unit: 50 m



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Sealing sections made of solid rubber with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 9844	Clamping range: 1.0–2.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 0845*	Clamping range: 0.8–2.5 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9845	Clamping range: 1.0–3.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 0841*	Clamping range: 1.0–2.5 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9581*	Clamping range: 2.0–5.0 mm NBR/soft rubber/micro- cellular rubber black Wire clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Sealing sections made of solid rubber with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 9846	Clamping range: 1.0–3.5 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9161*	Clamping range: 2.0–4.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 0842*	Clamping range: 2.0–4.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9904	Clamping range: 2.0–4.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9847	Clamping range: 3.0–5.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Sealing sections made of solid rubber with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 0846*	Clamping range: 1.0–3.5 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9122*	Clamping range: 1.0–2.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9848	Clamping range: 1.0–3.5 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9860	Clamping range: 1.0–3.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9001	Clamping range: 1.0–2.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Sealing sections made of solid rubber with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 9876	Clamping range: 1.0–4.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9540*	Clamping range: 1.5–3.5 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9858	Clamping range: 1.5–4.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9534	Clamping range: 1.5 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9862 Steel clamping strip 161 9863 Wire clamping strip	Clamping range: 1.0–3.5 mm EPDM/soft rubber/ microcellular rubber black Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Sealing sections made of solid rubber with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 9865	Clamping range: 1.5–4.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9851	Clamping range: 1.5–4.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9859	Clamping range: 1.5–4.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9855	Clamping range: 1.0–3.5 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9864	Clamping range: 1.5–4.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Sealing sections made of solid rubber with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 9013*	Clamping range: 1.0–2.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9676	Clamping range: 3.0 mm EPDM/soft rubber/ microcellular rubber black Wire strip with melt fibres Sales unit: 50 m
		161 9199* Clamping range: 2.0–4.0 mm 161 9889 Clamping range: 1.0–2.0 mm	EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9849	Clamping range: 2.0–4.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request

* Available from stock

Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Sealing sections made of solid rubber with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 9850	Clamping range: 1.0–3.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9861	Clamping range: 1.0–3.5 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9583*	Clamping range: 1.0–2.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9639*	Clamping range: 2.0–5.5 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9857	Clamping range: 1.5–4.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Sealing sections made of solid rubber with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 9852	Clamping range: 1.0–3.5 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9870	Clamping range: 1.5–4.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9675	Clamping range: 1.0–2.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9100*	Clamping range: 1.0–2.5 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9856	Clamping range: 1.5–4.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Sealing sections made of solid rubber with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 9871	Clamping range: 2.0–4.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9868	Clamping range: 1.5–5.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9853	Clamping range: 1.0–3.5 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9578	Clamping range: 2.0–5.5 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9837	Clamping range: 2.0–3.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Sealing sections made of solid rubber with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 9875	Clamping range: 2.5–5.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9854	Clamping range: 1.0–3.5 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9866	Clamping range: 1.0–4.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9759	Clamping range: 1.0–2.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request

* Available from stock

Issued 09-2013



TECHNOPROFIL®

TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0

Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de

web: www.technoprofil.com

Derken 8

42327 Wuppertal-Vohwinkel

Sealing sections made of solid rubber with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
	R60	161 0847*	Clamping range: 1.0–3.5 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
	R150 R100	161 9867	Clamping range: 1.5–4.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
	R130 R110 R50	161 9874	Clamping range: 2.0–4.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
	R60	161 9896	Clamping range: 1.0–2.5 mm EPDM/soft rubber/ microcellular rubber black with butyl sealing cord Steel clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request

* Available from stock

Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Sealing sections made of solid rubber with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 9872	Clamping range: 2.0–4.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9873	Clamping range: 2.0–4.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9322*	Clamping range: 1.5 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 0160*	Clamping range: 0.8–2.5 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request

* Available from stock

Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Sealing sections made of solid rubber with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 9812	Clamping range: 1.0–2.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9807	Clamping range: 1.0–2.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9808	Clamping range: 1.0–3.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 0844* EPDM/soft rubber/ microcellular rubber 161 9811 NBR/soft rubber/ microcellular rubber	Clamping range: 1.0–2.5 mm black Wire clamping strip Sales unit: 50 m
		161 9170*	Clamping range: 1.0–2.5 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Sealing sections made of solid rubber with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 9140*	Clamping range: 1.5–3.5 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9810	Clamping range: 1.0–2.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9815	Clamping range: 1.5–3.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9818	Clamping range: 1.0–3.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9813	Clamping range: 1.0–3.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



TECHNOPROFIL
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Sealing sections made of solid rubber with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 9816 Wire clamping strip Clamping range: 1.5–4.0 mm 161 9817 Steel clamping strip Clamping range: 1.0–3.5 mm	EPDM/soft rubber/ microcellular rubber black Sales unit: 50 m
		161 9814	Clamping range: 1.0–3.5 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9355*	Clamping range: 1.0–3.5 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9819	Clamping range: 1.0–3.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9410	Clamping range: 1.5 mm CR soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Sealing sections made of solid rubber with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 9686	Clamping range: 3.0–5.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9822	Clamping range: 1.0–3.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9697	Clamping range: 2.0–4.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9820 Steel clamping strip 161 9821 Wire clamping strip	Clamping range: 1.0–4.0 mm EPDM/soft rubber/ microcellular rubber black Sales unit: 50 m
		161 9834	Clamping range: 1.5–3.5 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Sealing sections made of solid rubber with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 0159*	Clamping range: 1.5–3.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9833	Clamping range: 1.0–3.5 mm CR soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9698	Clamping range: 1.5–3.5 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9690	Clamping range: 3.0–5.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9678	Clamping range: 1.0–3.5 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Sealing sections made of solid rubber with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 9647*	Clamping range: 5.0–8.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9680	Clamping range: 4.0–6.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9408*	Clamping range: 1.5–3.5 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9685	Clamping range: 2.0–5.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 0161*	Clamping range: 1.0–3.5 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Sealing sections made of solid rubber with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 9835	Clamping range: 1.5–3.5 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9688	Clamping range: 3.0–5.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9689	Clamping range: 3.0–5.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9691	Clamping range: 2.0–4.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9836	Clamping range: 1.5–4.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Sealing sections made of solid rubber with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 9823 Steel clamping strip 161 9824 Wire clamping strip	Clamping range: 1.0–4.0 mm EPDM/soft rubber/ microcellular rubber black Sales unit: 50 m
		161 9679	Clamping range: 1.0–4.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9723	Clamping range: 1.5–4.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9565	Clamping range: 3.0–6.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9489*	Clamping range: 5.0–9.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Sealing sections made of solid rubber with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 9828	Clamping range: 1.0–4.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9829	Clamping range: 1.0–4.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9722	Clamping range: 1.5–4.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9683	Clamping range: 2.0–4.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9732	Clamping range: 1.0–3.5 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Sealing sections made of solid rubber with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 0155* Clamping range: 4.0–6.0 mm 161 9743* Clamping range: 2.0–4.0 mm	EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9652*	Clamping range: 3.0–6.0 mm EPDM/soft rubber/ microcellular rubber black Segmented steel clamping strip Sales unit: 50 m
		161 9832	Clamping range: 2.0–4.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9682	Clamping range: 3.0–5.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9687	Clamping range: 4.0–6.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Sealing sections made of solid rubber with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 9344	Clamping range: 1.5 mm CR soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9619	Clamping range: 3.5–6.5 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9693	Clamping range: 2.0–4.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 0152*	Clamping range: 2.0–4.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9486*	Clamping range: 2.0–4.0 mm EPDM/soft rubber/ microcellular rubber black Segmented steel clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
 * Available from stock, subject to prior sale
 Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Sealing sections made of solid rubber with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 9694 Steel clamping strip 161 9839 Wire clamping strip	Clamping range: 1.5–4.0 mm EPDM/soft rubber/ microcellular rubber black Sales unit: 50 m
		161 9702	Clamping range: 1.0–4.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9681	Clamping range: 2.0–4.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9898	Clamping range: 1.5–3.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9607	Clamping range: 4.5–8.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Sealing sections made of solid rubber with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 9699	Clamping range: 2.5–5.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9648	Clamping range: 2.5–4.5 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9677	Clamping range: 1.5 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9830	Clamping range: 1.5–4.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9825 Steel clamping strip 161 9826 Wire clamping strip	Clamping range: 1.0–4.0 mm EPDM/soft rubber/ microcellular rubber black Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Sealing sections made of solid rubber with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 9715	Clamping range: 2.0–5.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9567	Clamping range: 0.8 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9908	Clamping range: 1,0 mm EPDM/soft rubber/ microcellular rubber Steel clamping strip Sales unit: 50 m
		161 9703	Clamping range: 1.5–4.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9733	Clamping range: 1.5–3.5 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Sealing sections made of solid rubber with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 9701	Clamping range: 1.0–3.5 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9704	Clamping range: 1.5–3.5 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9724	Clamping range: 1.5–4.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9707	Clamping range: 2.0–4.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9713	Clamping range: 3.0–5.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Sealing sections made of solid rubber with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 9705	Clamping range: 2.0–4.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9891	Clamping range: 2.0–4.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9700 Wire clamping strip 161 9840 Steel clamping strip	Clamping range: 1.5–4.0 mm EPDM/soft rubber/ microcellular rubber black Sales unit: 50 m
		161 9720	Clamping range: 6.0–8.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9706	Clamping range: 1.5–3.5 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Sealing sections made of solid rubber with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 9714	Clamping range: 4.0–6.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9709	Clamping range: 1.5–4.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9674	Clamping range: 2.5 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9748	Clamping range: 1.0–2.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9533	Clamping range: 1.0–2.5 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Sealing sections made of solid rubber with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 9827	Clamping range: 2.0–4.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9710	Clamping range: 1.5–4.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9730	Clamping range: 2.0–4.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9718 Steel clamping strip (R120 + R80) 161 9719 Wire clamping strip (R70 + R40)	Clamping range: 1.5–4.0 mm EPDM/soft rubber/ microcellular rubber black Sales unit: 50 m
		161 9695 Steel clamping strip 161 9696 Wire clamping strip	Clamping range: 1.5–4.0 mm EPDM/soft rubber/ microcellular rubber black Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Sealing sections made of solid rubber with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 9749	Clamping range: 1.0–2.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9708	Clamping range: 2.0–4.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9712	Clamping range: 4.0–6.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9716	Clamping range: 1.5–4.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9727	Clamping range: 2.0–4.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Sealing sections made of solid rubber with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 9729	Clamping range: 1.0–4.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9717	Clamping range: 6.0–8.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9726	Clamping range: 2.0–4.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9645	Clamping range: 1.5–2.5 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9838	Clamping range: 3.0–4.5 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Sealing sections made of solid rubber with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 9728	Clamping range: 1.5–3.5 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9642	Clamping range: 0.8 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9725	Clamping range: 1.5–4.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9711	Clamping range: 2.0–4.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9684	Clamping range: 3.0–5.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Sealing sections made of solid rubber with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 9618	Clamping range: 3.0–5.5 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9731	Clamping range: 1.0–4.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9753*	Clamping range: 1.0–2.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9083*	Clamping range: 1.0–2.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Sealing sections made of solid rubber with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 9721	Clamping range: 6.0–8.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9404	Clamping range: 1.5–3.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Sealing sections made of solid rubber with embedded steel clamping strips and microcellular rubber sealing area

Design	Bend radius	Item no.	Technical data
		161 9369*	Clamping range: 1.8 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 100 m
		161 0644*	Clamping range: 1.0–3.5 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 0642*	Clamping range: 1.0–2.5 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9735	Clamping range: 2.0–4.0 mm EPDM/soft rubber/ microcellular rubber black Segmented steel clamping strip Sales unit: 50 m
		161 9737	Clamping range: 2.0–5.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
 * Available from stock, subject to prior sale
 Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Sealing sections made of solid rubber with embedded metal clamping strips

Design	Bend radius	Item no.	Technical data
		161 9734	Clamping range: 2.0–4.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9736	Clamping range: 1.0–3.5 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9738	Clamping range: 2.0–4.0 mm EPDM/soft rubber/ microcellular rubber black Wire clamping strip Sales unit: 50 m
		161 9577*	Clamping range: 2.0–5.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m
		161 9739	Clamping range: 2.0–4.0 mm EPDM/soft rubber/ microcellular rubber black Steel clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Sealing sections made of solid rubber with embedded metal clamping strips

Design	Bend radius	Item no.	Technical data
		161 0650*	Clamping range: 1.0–2.0 mm EPDM soft rubber black Steel clamping strip Sales unit: 50 m
		161 0530*	Clamping range: 1.0–2.0 mm EPDM soft rubber black Steel clamping strip Sales unit: 50 m
		161 9646*	Clamping range: 1.0–2.5 mm EPDM soft rubber black Stainless steel wire clamping strip Sales unit: 50 m
		161 9882	Clamping range: 1.5–3.0 mm EPDM soft rubber black Steel clamping strip Sales unit: 50 m
		161 9023	Clamping range: 1.0–2.0 mm EPDM soft rubber black Steel clamping strip Sales unit: 15 m

All sections are shown in 1:1 scale.

Minimum order quantities on request
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Sealing sections made of solid rubber with embedded metal clamping strips

Design	Bend radius	Item no.	Technical data
	R50	161 9842	Clamping range: 1.5–3.0 mm EPDM soft rubber black Wire clamping strip Sales unit: 50 m
	R30	161 9843	Clamping range: 1.5–3.0 mm EPDM soft rubber black Steel clamping strip Sales unit: 50 m
	R40	161 9535*	Clamping range: 3.0 mm EPDM soft rubber black Steel clamping strip Sales unit: 30 m



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Sealing sections made of solid rubber with embedded metal clamping strips

Design	Bend radius	Item no.	Technical data
	R15	161 0350* EPDM soft rubber 161 9350* NBR (oil resistant)	Clamping range: 0.5–2.0 mm black Steel clamping strip Sales unit: 50 m
	R50	161 9878*	Clamping range: 3.0–4.0 mm EPDM soft rubber black Wire clamping strip Sales unit: 50 m
	R25	161 9002	Clamping range: 0.5–2.0 mm EPDM soft rubber black Wire clamping strip Sales unit: 20 m
	R50	161 9877	Clamping range: 3.0–4.0 mm EPDM soft rubber black Wire clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Sealing sections made of solid rubber with embedded metal clamping strips

Design	Bend radius	Item no.	Technical data
	R30	161 9741	Clamping range: 1.5–3.0 mm EPDM soft rubber black Steel clamping strip Sales unit: 50 m
	R60 R80	161 9751*	Clamping range: 1.0–2.5 mm EPDM soft rubber black Wire clamping strip Sales unit: 50 m
	R120 R50	161 9841	Clamping range: 2.0–5.0 mm EPDM soft rubber black Steel clamping strip Sales unit: 50 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Sealing sections made of solid rubber without clampfitting

Design	Bend radius	Item No.	Technical data
		103 9664	Clamping range: 0,8-1,3 mm EPDM soft rubber black 90/65 Shore A Sales unit: 50 m
		103 9707	Clamping range: 0,8-1,3 mm EPDM soft rubber black 90/70 Shore A Sales unit: 50 m



technoprofil
TP Blau GmbH

Tel.: +49 (0) 2 02 / 27 34 6-0
Fax: +49 (0) 2 02 / 27 34 6-60

E-Mail: info@technoprofil.de
web: www.technoprofil.com

Derken 8
42327 Wuppertal-Vohwinkel

Sealing sections made of silicone with embedded metal clamping strips

Design	Bend radius	Item no.	Technical data
		106 9002	Clamping range: 2.0 mm Silicone grey white RAL 9002 Wire clamping strip Sales unit: 50 m
		106 9006	Clamping range: 0.8–2.0 mm Silicone 60 Shore A grey RAL 7021 Wire clamping strip Sales unit: 25 m
		106 9003	Clamping range: 1.5–3.0 mm Silicone black Wire clamping strip Sales unit: 50 m
		161 9346	Clamping range: 0.5–2.0 mm Silicone black Wire clamping strip Sales unit: 25 m

All sections are shown in 1:1 scale

x = clamping range

Minimum order quantities on request
* Available from stock, subject to prior sale
Issued 09-2013